

|                                |                                         |                                                                                 |
|--------------------------------|-----------------------------------------|---------------------------------------------------------------------------------|
| <b>Crane capacity</b>          |                                         | 5.5t×1.8m<br>12125lbs×1.8m                                                      |
| <b>Max raising height</b>      |                                         | 16.9m/55ft                                                                      |
| <b>Max operating radius</b>    |                                         | 16m/52ft                                                                        |
| <b>Winch</b>                   | <b>Hook up speed</b>                    | 10m/min (4 falls)                                                               |
|                                | <b>Diameter and length of wire rope</b> | 10mm×80m                                                                        |
| <b>Telescopic</b>              | <b>Boom form</b>                        | 5 sections with fly jib                                                         |
|                                | <b>Boom length</b>                      | 16.6m/54ft                                                                      |
| <b>Derrick</b>                 | <b>Derricking angle</b>                 | 0-80°                                                                           |
| <b>Slewing</b>                 | <b>Slewing angle</b>                    | 360-degree continuous                                                           |
| <b>Outrigger</b>               | <b>Form of outrigger</b>                | Fully automatic                                                                 |
|                                | <b>Maximum extend range</b>             | 5170×5807× 5423mm<br>17'×19'×17'9"                                              |
| <b>Traction system</b>         | <b>Travel</b>                           | Hydraulic                                                                       |
|                                | <b>Travel speed</b>                     | 0-3km/h                                                                         |
|                                | <b>Track</b>                            | Synthetic rubber                                                                |
|                                | <b>Grade ability</b>                    | 32%                                                                             |
|                                | <b>Track ground pressure</b>            | 41.3Kpa                                                                         |
| <b>Hydraulic Tank capacity</b> |                                         | 90L                                                                             |
| <b>L×W×H</b>                   |                                         | 4960x1370x1980 (mm)<br>16'×54"×6'6"                                             |
| <b>Total weight</b>            |                                         | 5500Kg/12125lbs                                                                 |
| <b>Safety device</b>           |                                         | Torque limiter Height limiter<br>Safety protection valve<br>Anti-tip-over alarm |
| <b>Optional</b>                |                                         | White-colored crawlers Glass lifter                                             |